



This is to certify, that the undernoted products have been approved in accordance with the relevant requirements of the GL Approval System.

Certificate No.

20 107 - 11 HH

Company

eka-edelstahlkamine gmbH

Robert - Bosch - Str. 4

95369 Untersteinach, GERMANY

Product

Exhaust Gas System

Type

complex medi D (double wall) complex medi E (single wall)

Technical Data /

Application

TECHNICAL DATA

Materials:

AISI 316L/316Ti/304H (1.4404, 1.4571,1.4948) Inner pipe

Outer pipe

AISI 304 (1.4301), AISI 316L/316Ti (1.4404, 1.4571)

Thickness

0.6mm (minimum) outside, 0.5 mm inside

Insulation:

Type approved pre-formed mineral fibre

Min. thickness 30 mm Min. density

90 kg/m³

Sealing Materials: Size range:

Asplit (up to 600°C) 80 mm up to 500 mm

M.A.W.P. / M.A.W.T.: 5000 Pa / 600 °C

Range of Application:

The piping systems of type complex medi are approved for the use as exhaust gas

lines on boilers and diesel engines (downstream of turbo chargers).

Approval Standard

DIN EN 1856-1: 2009, DIN EN 1859: 2009, DIN EN 13216-1:2004

Documents

- Test reports: TÜV SÜD test report no.: A 1348-00/04, dated: 28.12.2004

- Test report: paconsult test report no.: 10-3061, dated: 30.08.2011

- Certificate: TÜV SÜD Cert. 0036 CPD 90216 004, dated: 17.02.2010

- Drawings of piping systems, technical data sheet of sealing material

Remarks

For penetration of fire divisions GL type approved pipe penetrations are to be used

Valid until

2016-09-02

File No.

XI.B.03

Germanischer Lloyd

Hamburg, 2011-09-02

Hanspeter Raschle

Approval Certificate



Certificate No.

20 107 - 11 HH

PRODUCTION PLACE

eka-edelstahlkamine gmbh Robert - Bosch - Str. 4 95369 Untersteinach GERMANY

MARKING

Each device shall bear legible and durable marking on the body or on a plate fixed securely to the body as follows:

• Manufacturer's Mark • Identity Number • Nominal Diameter • GL Certificate No. •

REMARKS / LIMITATIONS

• The selection of the Exhaust Gas System for the corresponding application and the right installation are to be in accordance with the instructions of the manufacturer.

Germanischer Lloyd

Hamburg, 2011-09-02

Hanspeter Raschle

Peter Gierhan

Page 2 of 2