



This is to certify, that the undernoted products have been approved in accordance with the relevant requirements of the GL Approval System.

Certificate No.

11 795 - 10 HH

Company

eka-edelstahlkamine gmbH

Robert - Bosch - Str. 4

95369 Untersteinach, GERMANY

Product

Exhaust Gas System

Type

complex Europ D (double wall) complex Europ E (single wall)

Technical Data / Application

TECHNICAL DATA

Materials: Inner pipe

AISI 316L/316Ti/304H (1.4404, 1.4571,1.4948)

Outer pipe

AISI 304 (1.4301), AISI 316L/316Ti (1.4404, 1.4571)

Thickness

0.6mm (minimum) outside, 1,0 mm inside

Insulation:

Type approved pre-formed mineral fibre

Min. thickness 50 mm

Min. density

90 kg/m³

Sealing Materials:

Asplit (up to 600°C) Silicone (up to 200°C)

Size range :

150 mm up to 1000 mm

M.A.W.P. / M.A.W.T.: 5000 Pa / 600 °C

Range of Application:

The piping systems of type complex medi are approved for the use as exhaust gas

lines on boilers and diesel engines (downstream of turbo chargers).

Approval Standard

DIN EN 1856-1: 2003, DIN EN 1859: 2000, DIN EN 13216-1:2004

Documents

- Test reports: TÜV SÜD test report no.: A 1812-00/09, dated: 02.09.2009

- Certificate: TÜV SÜD Cert. 0036 CPD 90216 008, dated: 09.10.2009

- Drawings of piping systems, technical data sheet of sealing material and

installation instructions

Remarks

For penetration of fire divisions GL type approved pipe penetrations are to be used

Valid until

2015-08-20

File No.

XI.B.03

Germanischer Lloyd

Hamburg, 2010-08-20

Hanspeter Raschle

Peter Gierhan

Approval Certificate



Certificate No.

11 795 - 10 HH

PRODUCTION PLACE

eka-edelstahlkamine gmbh Robert - Bosch - Str. 4 95369 Untersteinach GERMANY

MARKING

Each device shall bear legible and durable marking on the body or on a plate fixed securely to the body as follows:

• Manufacturer's Mark • Identity Number • Nominal Diameter • GL Certificate No. •

REMARKS / LIMITATIONS

• The selection of the Exhaust Gas System for the corresponding application and the right installation are to be in accordance with the instructions of the manufacturer.

Germanischer Lloyd

Hamburg, 2010-08-20

Hanspeter Raschle

Peter Gierhan